


Pump head inlet Supplement





Note: Please read the corresponding technical documentation for handling and safety reasons.

Technical support:

Phone: +49 30 809727-111 (workdays 9-17h CET)

Fax : +49 30 8015010

Email: support@knauer.net

Publisher:

KNAUER Wissenschaftliche Geräte GmbH

Hegauer Weg 38

14163 Berlin

Germany

Phone: +49 30 809727-0

Fax: +49 30 8015010

Internet: www.knauer.net

E-Mail: info@knauer.net

Version information:

Document number: V6844

Version number: 1.2

Release date: 2022/09/26



The information in this document is subject to change without prior notice. For the latest version of the instructions, visit our website: www.knauer.net/library.

Table of Contents

NOTE! For your own safety, read the manual and always observe the warnings and safety information on the device and in the manual!

Product Information	4
About the Supplement	4
Intended Use	4
Installation	5
Inserting the Seals	6
Mounting the Pump Head Inlet	8
Attaching the Tubing to the Stainless Steel Pump Head Inlet	9
Attaching the Nut to the PEEK Pump Head Inlet ..	10
Order Numbers	12

Product Information

The product information contain useful and obligatory details about the product, the delivery and the documentation.

About the Supplement

This supplement uses common abbreviations, which are listed below:

Abbreviation	Meaning
OD	outer diameter
ID	inner diameter
A/F	wrench size
PEEK	polyether ether keton: biocompatible material for the pump head inlet
PCTFE	polychlorotrifluorethylene: biocompatible material for the ferrule and the nut

Intended Use

The pump head inlet is an accessory for preparative KNAUER pumps. It spreads solvents entering through a tubing into both pump head channels.

The stainless steel pump head inlet consists of a thread for male connectors with 1/4" NPT outer thread. You can use male connectors for tubings with 1/8" OD, 4 mm OD, or 1/4" OD.

The PEEK pump head inlet consists of a thread for male connectors with 1/2-20 UNF thread. A matching bushing for tubing with 1/4" OD is part of the delivery.

Installation

Verify that the package is complete according to the packing list before starting the installation. The scope of delivery includes all components that you need for a safe assembly and as a protection from extruding liquids. Subsequently, you find the description on how to connect a 1/4" tubing with the matching male connector to the pump head inlet.





Fig. 2 Delivery for PEEK pump head inlet

① Bushings

② Seals

③ Ferrule and nut

④ Intake manifold

Inserting the Seals


The intake manifold is screwed to the pump head with two bushings through which the eluent flows into the pump head. To guarantee usage without leaks, you have to apply seals on both sides of the intake manifold.

Material


- Four seals
- Intake manifold
- Two bushings

Process

1. Lay two of the seals ① onto the intake manifold.
2. Slide the other two seals ② each onto the thread of one bushing.



3. Lift the intake manifold ③ and guide the bushings through the openings as indicated by the arrow.

**Next Steps**

Mount the pump head inlet to the pump head.

Mounting the Pump Head Inlet

Pay attention to the different torques for the bushing which depends on the pump head inlet material:


Material	Torque
Stainless steel	7.5 Nm
PEEK	5 Nm

Tools

Torque wrench, size 17

Process

1. Fit the pump head inlet ① precisely to the bottom side of the pump head.
2. Using the torque wrench ②, tighten the bushing.



Next Steps

Fasten the tubing using the male connector. Find below the description for the stainless steel pump

head inlet, or go to page 10 for the PEEK pump head inlet.

Attaching the Tubing to the Stainless Steel Pump Head Inlet

KNAUER offers male connectors and tubings in different sizes. You find the order numbers and further details in chapter "Order Numbers" on page 12.

NOTE **The male connector and the tubing are accessories and hence not included with the delivery.**

Material


- Male connector with 1/4" NPT outer thread
- Teflon sealing tape

Tools

- Open-end wrench, size 17

Process

1. Cut a small strip off the sealing tape and wrap the thread ① of the male connector.



Process

2. Screw the male connector ② into the side opening of the pump head inlet. Using the open-end wrench, tighten the stainless steel connector.

**Next Steps**

Connect the tubing to a solvent bottle. Pay attention to the information in the user manual before taking the pump into operation.

Attaching the Nut to the PEEK Pump Head Inlet

The nut for the PEEK pump head inlet is part of the delivery.

Material

- Ferrule
- Nut

Process

1. Slide the nut ② with the head up front over the tubing. Afterwards, push the ferrule ① onto the tip of the tubing.



2. Screw the nut into the side opening of the pump head inlet. Tighten the nut by hand.

Next Steps

Connect the tubing to a solvent bottle. Pay attention to the information in the user manual before taking the pump into operation.

Order Numbers

Spare parts

Name	Order no.
Pump head inlet, stainless steel	A9861
Intake manifold, stainless steel	G1468
Pump head inlet, PEEK	A9868
Intake manifold, PEEK	G1468A
Ferrule	M2757
Nut	M2758

Accessories

Name	Order no.
Male connector connection for tubing with 1/4" OD	A58267
Tubing for A58267 PTFE, 1/4" OD, 4.8 mm ID	U0435
Male connector connection for tubing with 4 mm OD	A58268
Tubing for A58268 PTFE, 4 mm OD, 3 mm ID	U0312
Male connector connection for tubing with 1/8" OD	A58269
Tubing for A58269 FEP, 1/8" OD, 2.1 mm ID	U0452

atest KNAUER instructions online:
www.knauer.net/library

© KNAUER 2022

KNAUER
Wissenschaftliche Geräte GmbH
Hegauer Weg 38
14163 Berlin

Phone: +49 30 809727-0
Fax: +49 30 8015010
E-Mail: info@knauer.net
Internet: www.knauer.net